

SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: AMERIGUARD Fleet 10W-30
Product Code: AG-1030FL-XX

NFPA Hazard identification 0-Least 1 – Slight 2 – Moderate 3-High 4- Extreme

HEALTH: 0 **FIRE: 1** **REACTIVITY: 0**

COMPANY IDENTIFICATION

Company: SAPP BROS., INC.
9915 S. 148th Street
Omaha, Nebraska 68138 USA

Emergency Phone:	(800) 424-9300 (202) 483-7616 (CHEMTREC)
Poison Control Center:	(800) 222-1222
Information hone:	(800) 233-4059 (402) 895-2202
MSDS Internet Address	http://www.sappbros.net

SECTION 2

Composition Information on Ingredients

Component Name	%	CAS	OSHA PEL	ACGIH TLV
Lubricating Oil Base Stock	83-93	Mixture	5mg/m3*	5mg/m3*
Proprietary Additives	7-17	Mixture	5mg/m3*	5mg/m3*

NON-HAZARDOUS INGREDIENTS

No IARC, NTP OSHA and ACGIH Listed carcinogens

SECTION 3

Hazards Identification

EYE CONTACT: Contact with eyes may cause eye irritation.

SKIN CONTACT: Prolonged or repeated contact may result in skin irritation or dermatitis.

INHALATION: Breathing oil mist in concentrations that exceed the TLV and PEL may result in respiratory discomfort and irritation.

INGESTION: Although this product is not expected to be acutely toxic, aspiration of liquid into the lungs during ingestion or vomiting may cause chemical pneumonitis.

CARCINOGENICITY: This product has not been classified as a carcinogen or probable carcinogen by OSHA.

SIGNS AND SYMPTOMS OF OVEREXPOUSURE: May cause skin, eye, or respiratory irritation.

MEDICAL CONDISTIONS GENERALLY AGGRAVATED BY EXPOSURE: None recognized.

OTHER HEALTH INFORMATION: If splashed into the eyes, flush with water for 15 minutes or until irritation subsides. Get medical attention if irritation persists.

SECTION 4

FIRST AID MEASURES

EYE CONTACT: If splashed into the eyes, flush with water for 15 minutes or until irritation subsides. Get medical attention if irritation persists.

SKIN CONTACT: Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists.

INHALATION: If overcome by vapor from hot product, immediately remove victim to fresh air. If breathing has stopped, administer artificial respiration. Call for medical attention. If overexposed to oil mist, remove from further exposure.

INGESTION: DO NOT induce vomiting; call medical attention immediately.

SECTION 5

FIRE AND EXPLOSION HAZARD DATA

Flash Point (deg F): >420 Method Used: COC
Flammable or Explosive Limits (approximate % by volume in air) LEL: n/a UEL: n/a

EXTINGUISHING MEDIA: Use water spray, dry chemical, foam, or carbon dioxide. Use water to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures and to disperse vapors from spills or leaks.

SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus may be required.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not weld, heat or drill container. Residue may ignite with explosive force if heated sufficiently. Do not use pressure to empty drum or explosion may result.

SECTION 6

ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Add sand, earth, or other suitable absorbent to spill area. Keep product out of sewers and waterways by damming or impounding.

SECTION 7

HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place with adequate ventilation. Do not expose to extreme temperature of flames.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Use supplied-air respiratory protection in confined or enclosed space, if needed.

VENTILATION: Use local exhaust to capture vapor, mist or fume, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air.

PROTECTIVE GLOVES: Use neoprene gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION: Wear goggles if there is a likelihood of contact with eye(s).

OTHER PROTECTIVE EQUIPMENT: Use neoprene apron or other clothing, if needed, to avoid prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERING CONTROLS: Keep containers closed when not in use.

PERSONAL HYGIENE: Wash skin thoroughly after contact, before breaks and meals, and at the end of the work period. Thoroughly clean contaminated clothing, including shoes, before reuse.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (deg F): n/a

Specific Gravity (H₂O=1):.887

Vapor Pressure (mm Hg): n/a

Pour Point (deg F):-27

Vapor Density (Air=1): n/a

Solubility in Water: Insoluble

Evaporation Rate (n-butyl Acetate=1): n/a

APPEARANCE AND ODOR: Dark brown liquid, petroleum odor.

SECTION 10

STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal combustion forms carbon dioxide and water vapor and may produce oxides of sulfur, nitrogen, and phosphorus. Incomplete combustion can produce carbon monoxide. .

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

SECTION 11

TOXICOLOGICAL INFORMATION

See Section IV

SECTION 12

ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

MOBILITY

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Base oil component -- Expected to be inherently biodegradable.

SECTION 13

DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Place in an appropriate disposal facility in compliance with local regulations.

SECTION 14**TRANSPORT INFORMATION**

NOT A REGULATED ITEM ACCORDING TO DOT.

SECTION 15**REGULATORY INFORMATION**

SARA SECTION 313: This product contains from 0.5 to 1.4% zinc compounds.

WHMIS classification for product: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Updates made in accordance with implementation of GHS requirements.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate

Disclaimer: This material safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.

Internal Use Only	
MHC: 0B, 0B, 0, 0, 0, 0	PPEC: A

DGN: 7085202XUS (1014509)

Copyright 2010 Sapp Bros., Inc., All rights reserved