



Ameriguard Fleet

10W-30 & 15W-40



Ameriguard Fleet Engine Oil is a high quality, fleet engine oil formulated from premium hydro- treated base stocks and additives. Recommended for heavy duty diesel applications including low emission engine designs and those using EGR. These products have excellent dispersancy, with a TBN level of 10. This product is formulated to maintain the durability of emission control systems, including diesel particulate filters and other advanced aftertreatment systems.

Ameriguard Fleet 10W-30 & 15W-40 meets or exceeds the latest requirements of API CK-4, CJ-4, CI-4 Plus, CI-4, CH-4. Caterpillar ECF-3, Cummins CES 20086, 20081. Approved by the following OEMs: Mack EOS-4.5, EO-0 Premium Plus, Detroit Fluids 93K222, 93K218, Ford WSS M2C171-F1, MTU Oil Category 2.1 (15W-40 Only) Renault Trucks RLD-4, RLD-3, Volvo VDS-4.5, VDS-4.

Product Typical Specifications

Property	Test Methods	SAE Grade 15W-40	SAE Grade 10W-30
10			
Viscosity @100C, cSt	ASTM D-445	14.2	11.9
Viscosity@40C,cSt	ASTM D-4455	112	81.3
Viscosity Index	ASTMD-2270	132	140
CCS, cP	ASTM D-5293	5900 @20C	655 @ 25C
MRV, cP	ASTM D-4684	20000 @25C	22600@ 30C
Pour Point, C(F)	ASTM D-97	-27	-36
Flash Point, COC, C	ASTM D-92	225	225
Sulfated Ash, wt.%	ICP	1.0	1.0
TBN	ASTM D-2896	10	10

Distributed by SBP, 9915 So. 148th St. Omaha, Nebraska 68138
(1-800-233-4059)

Revised 5/30/2017